

AFL-15i-HM55/AFL-17i-HM55/AFL-19i-HM55

15" ~ 19" AFOLUX PPC features Intel® Core™ i7/i5/i3 mobile processor with Intel® HM55 chipset



Key Features

- 15"~19" multi-functional panel PC with touchscreen
- Powered by high performance Intel® mobile Core™ i7/ i5/ i3 and Celeron® processor with Intel® HM55 chipset
- System memory supports DDR3 SDRAM SO-DIMM up to 8 GB
- HDMI interface provides second display with vivid image quality
- 802.11 b/g/n high speed wireless
- Bluetooth V2.1+EDR
- Dual gigabit Ethernet
- Versatile mounting solution: panel/wall/rack/stand mounting
- IEI One Key Recovery solution allows you to create rapid OS backup and recovery



High-end Audio and Video Performance



Performance Leadership

- Arrandale on 32nm Processor
- Introduces DDR3 Support (800/1066)
- Enhanced Graphics Engine (Gen 5.7)

Increased Integration

- Full HD HW Acceleration
- Dedicated High Definition Display Interface (HDMI)



Dual Channel DDR3 Support up to 8 GB



Information



Digital Signage



KIOSK




Internet KIOSK

AFOLUX PPC Mobile Chipset Transition

The AFOLUX PPC *i* series features 2010 new Intel® Core™ processor with HM55 chipset. Advanced technologies like Hyper-Threading Technology and an integrated graphics core increase in graphics core effectiveness providing outstanding audio/video and processing performance.

	2008	2009	2010
Platform	Merom in Santa Rosa (GME965)	Penryn in Montevina (GM45)	Arrandale in Calpella (HM55)
CPU	Intel® Core™ 2 Duo Intel® Core™ 2 Duo LV Intel® Celeron® M	Intel® Core™ 2 Duo Intel® Core™ 2 Duo LV Intel® Core™ 2 Duo ULV Intel® Celeron® M Intel® Celeron® M ULV	Socket G1 for Intel® mobile Core™ i7/ i5/ i3 and Celeron® processor
Chipset	ICH8M-E	ICH9M	HM55
FSB	667/800 MHz	1066/800/667 MHz	N/A
TDP	35 W	17.5 W~47 W (CPU + GM45/GS45)	15~37W
Supported Memory	DDR2 667/800 (system max. 4 GB)	DDR2 667/800 (system max. 4 GB)	Two 204-pin 4 GB (max.) 800/1066 MHz dual-channel DDR3 SDRAM SO-DIMM supported (System max. 8 GB)
Graphics Cores	Gen 4.0	Gen 5.5 with 10 Execution Units DirectX10, Open GL 2.0	Gen 5.7 with 12 Execution Units DirectX10, Open GL 2.1
Second Display Interface	VGA	VGA, HDMI	VGA, HDMI
Intel® Active Management Technology (Intel™ AMT)	2.5	4	No

I/O Interface



Easily Accessible HDD and CF Card



Specifications

Model	AFL-15i(E)-HM55	AFL-17i-HM55	AFL-19i-HM55
LCD/Touch Specifications			
LCD Size	15"	17"	19"
Max. Resolution	1024 x 768	1280 x 1024	1280 x 1024
Brightness (cd/m ²)	350 or 250	350	450
Contrast Ratio	700:1 or 450:1	800 : 1	1000:1
LCD Color	262K or 16.7 M	16.7 M	16.7 M
Pixel Pitch (mm)	0.297(H) x 0.297(V)	0.264 (H) x 0.264 (V)	0.294(H) x 0.294(V)
Viewing Angle (H-V)	140°/125° or 120°/100°	160° / 160°	178° / 178°
Backlight MTBF	50000 hrs or 40000 hrs	50000 hrs	50000 hrs
Touch Screen	Resistive Type 5-wire (Touch controller IC is on board) or capacitive type touch screen without HDD bay		
System			
SBC Model	AFLMB2-HM55-R10		
CPU	Socket G (PGA989) Intel® Arrondale processor		
Chipset	Intel® HM55		
RAM	Two 204-pin 800/1066 DDR3 dual-channel SO-DIMMs supported (system max. 8 GB)		
I/O Ports	1 x RS-232 COM Port 1 x RS-232/422/485 COM Port 2 x RJ-45 for Giga LAN 4 x USB 2.0 1 x Power Switch 1 x Reset Button 1 x Audio Port (Line-Out) 1 x VGA 1 x Power Jack 1 x HDMI Port		
SSD	SATA SSD		
Watchdog Timer	Software programmable supports 1~255 sec. system reset		
Audio	AMP 3 W + 3 W (internal speaker)		
Expansion	1 x wireless Lan 802.11 b / g / n module (internal PCIe mini card interface) 1 x Bluetooth function (internal USB interface, Bluetooth V2.1+EDR)		
Drive Bay	1 x 2.5" SATA HDD bay		
Membrane Keypad	LCD on/off, brightness up/down, volume high/low (5 keys)		
LED Function	1 x Power on/off LED on front panel		
Wireless			
Wireless	1 x Wireless LAN 802.11 b/g/n module (internal PCIe mini card interface)		
Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x HSUPA mobile module (USB interface)		
Bluetooth	Bluetooth V2.1+EDR		
Physical			
Construction Front Panel	ABS + PC plastic front frame		
Mounting	Panel, Wall, Rack, Stand and Arm VESA 100 mm x 100 mm		
Front Panel Color	Sliver (877U) & Gray (ABSA2037)		
Dimensions (WxHxD) (mm)	394 x 309 x 75	428 x 350 x 76	470 x 383 x 79
Environment			
Operation Temperature (°C)	0°C ~ 50°C		
Storage Temperature (°C)	-20°C ~ 60°C		
Weight (N/G)	5.8 Kg	6.0 Kg	6.2 Kg
IP Level	Front frame IP64		
Safety & EMC	CE / FCC / CB / CCC		
Power			
Power Adapter	P/N: 63000-FSP096AHB-RS 96 W Power adapter Input: 90 VAC~264 VAC, 50/60 Hz Output: 12 VDC		
Power Requirement	12 VDC		
Power Consumption	80 W	85 W	87 W

Ordering Information

15" Regular Luminance (250cd/m ²)	AFL-15iE-HM55i3-33/R/2G-R10	15" 250cd/m ² XGA panel PC with Intel® Core™ i3-330M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
	AFL-15iE-HM55i5-52/R/2G-R10	15" 250cd/m ² XGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
	AFL-15iE-HM55i7-62/R/2G-R10	15" 250cd/m ² XGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
	AFL-15iE-HM55-P45/R/1G-R10	15" 250cd/m ² XGA panel PC with Intel® Celeron P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
15" High Luminance (350cd/m ²)	AFL-15i-HM55i3-33/R/2G-R10	15" 350cd/m ² XGA panel PC with Intel® Core™ i3-330M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
	AFL-15i-HM55i5-52/R/2G-R10	15" 350cd/m ² XGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
	AFL-15i-HM55i7-62/R/2G-R10	15" 350cd/m ² XGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
	AFL-15i-HM55P-P45/R/1G-R10	15" 350cd/m ² XGA panel PC with Intel® Celeron P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, RoHS
17" High Luminance (350cd/m ²)	AFL-17i-HM55i3-33/R/2G-R10	17" 350cd/m ² SXGA panel PC with Intel® Core™ i3-330M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
	AFL-17i-HM55i5-52/R/2G-R10	17" 350cd/m ² SXGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
	AFL-17i-HM55i7-62/R/2G-R10	17" 350cd/m ² SXGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
	AFL-17i-HM55-P45/R/1G-R10	17" 350cd/m ² SXGA panel PC with Intel® Celeron P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
19" High Luminance (450cd/m ²)	AFL-19i-HM55i3-33/R/2G-R10	19" 450cd/m ² SXGA panel PC with Intel® Core™ i3-330M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
	AFL-19i-HM55i5-52/R/2G-R10	19" 450cd/m ² SXGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
	AFL-19i-HM55i7-62/R/2G-R10	19" 450cd/m ² SXGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS
	AFL-19i-HM55-P45/R/1G-R10	19" 450cd/m ² SXGA panel PC with Intel® Celeron P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, bluetooth, R10, RoHS

Options

Model	AFL-15i-HM55	AFL-17i-HM55	AFL-19i-HM55
Panel Mounting Kit	AFLPK-19B		
Wall Mounting Kit	AFLWK-19 / AFLWK-19B		
Rack Mounting Kit	AFLRK-15B	AFLRK-17B	N/A
ARM	ARM-11-RS, ARM-31-RS		
Stand	STAND-A19, STAND-B19, STAND-C19, STAND-210-R11		
OS: Win XPE	AFLSD-15-HM55-2G-XPE (2 GB SATA SSD module)	AFLSD-17-HM55-2G-XPE (2 GB SATA SSD module)	AFLSD-19-HM55-2G-XPE (2 GB SATA SSD module)
OS: Win	AFLSD-15-HM55-4G-WES7E-R10 (4 GB SATA SSD module)	AFLSD-17-HM55-4G-WES7E-R10 (4 GB SATA SSD module)	AFLSD-19-HM55-4G-WES7E-R10 (4 GB SATA SSD module)
Hybrid Card Reader	AFLP-19AMSI-U		
Magnetic Stripe Reader	AFLP-19AMSR-U		
DC 12 V Input UPS	AUPS-B10-R10 (VESA 100, DC 12 V input, 12 V output 100 W UPS module with 3800 mAh)		
DC 9~36 V Input UPS	AUPS-B20-R10 (VESA 100, DC 9~36 V input, 12 V output 100 W UPS module with 3800 mAh)		

Packing List

Item	Part Number	Q'ty	Specifications
Power Cord	32000-000002-RS	1	1750 mm; European Standard
Power Adapter	63000-FSP096AHB-RS	1	90~264 V AC Input; 12 V DC Output; 96 W
Utilities CDROM	7B000-000087-RS	1	
Screw Kit	44013-030041-RS	1	
Touch Pen	43125-0002C0-00-RS	1	
Remote Controller	7Z000-8T00320ICP05G-RS	1	