## Convision V600 Plus Series

Convision V400 Plus - Convision V610 Plus



4-6 Channel IP Video Server with Realtime Motion Detection

Innovative Live JPEG compression

Alarming/recording/playback/remote

Video evaluation via motion and event histogram

Extensible hard disk capacity up to 8 TB via IEEE 1394

Extended Dome/PTZ support

System auto recovery in one minute

Embedded operating system



## Convision V600 Plus Series

Convision V400 Plus - Convision V610 Plus

System	
Operating System	Real time operating system
Video Input	4-6 BNC
Video Output	1 BNC
Video Format	PAL
Compression	JPEG
User Interface	Web browser interface
Security	User administration
WatchDog	Software and hardware watchdog
Monitoring Mode	
Frame Rate	3fps/cam
Resolution	704x576, 352x288
Split Layout	1/4/6
HD Status	Yes
Video Loss Detection	Yes
Recording Mode	
Resolution	704x576, 352x288
Recording Speed	3fps/cam
Hard Disk Storage Capacity	80-120Gbyte internal, 8TB external via IEEE1394
Recording Modes	Motion Detection, long term, event
Data Code	Recording includes time/date information
Remote Functions	
Network Access	10/100 Mbit Ethernet
Monitoring	Web browser, no software required
Playback	Live JPEG via web browser
Download and Local Playback	Evaluation via ConvisionSafe
Alarm Functions	
Alarm Input	4 NC/NO digital inputs
Alarm Output	4 NC/NO relay out
IO and Camera Relations	1-1, 1-n
Others	
Serial Ports	1x RS232, 1x RS485
Dome Support	Current list under www.convision.com
Power Consumption	Convision V610 Plus: 12W
Dimensions	W: 163mm, H: 80mm, D: 185mm
Weight	Convision V610 Plus: 1450g
Operating Temperature	0°C ~ +40°C



Your Dealer:



## Convision V1600 Series

Convision V800 - Convision V1600



8-16 Channel IP Video Server with Realtime Motion Detection

Innovative Live JPEG compression

Alarming/recording/playback/remote

Video evaluation via motion and event histogram

Extensible hard disk capacity up to 8 TB via IEEE 1394

Extended Dome/PTZ support

System auto recovery in one minute

Embedded operating system



## Convision V1600 Series

Convision V800 - Convision V1600

System	
Operating System	Real time operating system
Video Input	8-16 BNC
Video Output	2 BNC
Video Format	PAL
Compression	JPEG
User Interface	Web browser interface
Security	User administration
WatchDog	Software and hardware watchdog
Monitoring Mode	
Frame Rate	64fps (8fps/cam) V800, 64fps (4fps/cam) V1600
Resolution	(704x576), 352x288
Split Layout	1/4/8/16
HD Status	Yes
Video Loss Detection	Yes
Recording Mode	
Resolution	352x288
Recording Speed	64fps (8fps/cam) V800, 64fps (4fps/cam) V1600
Hard Disk Storage Capacity	160-500Gbyte internal, 8TB external via IEEE1394
Recording Modes	Motion Detection, long term, event
Data Code	Recording includes time/date information
Remote Functions	
Network Access	10/100 Mbit Ethernet
Monitoring	Web browser, no software required
Playback	Live JPEG via web browser
Download and Local Playback	Evaluation via ConvisionSafe
Alarm Functions	
Alarm Input	4 NC/NO digital inputs
Alarm Output	4 NC/NO relay out
IO and Camera Relations	1-1, 1-n
Others	
Serial Ports	1x RS232, 1x RS485
Dome Support	Current list under www.convision.com
Power Consumption	Convision V1600: 20W
Dimensions	W: 163mm, H: 80mm, D: 185mm
Weight	Convision V1600: 5900g
Operating Temperature	0°C ~ +40°C



Your Dealer:

