







AIRPORT EQUIPMENT GMBH

FREIGHT HANDLING WITH OUTSTANDING RELIABILITY

The CHAMP 70, TREPEL's 7 ton cargo high loader range, combines highest availability with extremely low operation and maintenance costs, making this versatile Pallet and Container high loader a real CHAMP. Fast lifting speed as well as accurate freight transfer under all climatic conditions are true operational advantages. The design of the CHAMP 70 offers maximum safety for operating personnel, aircraft and loader. These performances bring freight handling to higher levels.

Performance	CHAMP 70S	CHAMP 70W	CHAMP 70U
Dimensions I x w x h	9.20 x 3.60 x 3.10 m	9.20 x 4.30 x 3.10 m	9.20 x 4.30 x 3.20 m
Capacity	7.000 kg	7.000 kg	7.000 kg
Lifting height front platform	1.800 to 3.700 mm	1.800 to 3.700 mm	1.900 to 5.600 mm
Lifting height main platform	485 to 3.700 mm	485 to 3.700 mm	485 to 3.700 mm
Loading width (between guide rails)	2.520 mm	3.300 mm	3.300 mm
Driving speed	15 km/h	15 km/h	15 km/h
Gradability	6 %	6 %	6 %
Turning radius	9.200 mm	9.600 mm	9.600 mm

Design

Engine Deutz 4-cylinder diesel type BF4L2011 (COM II, EPA-TIR II)

Transmission / axles Open circuit hydrostatic drive system on front axle

Steering Hydraulic powered steering

Braking system Dual-circuit hydraulic multiple disc brake,

additional spring-loaded emergency parking brake

Stabilisers 6 hydraulically operated stabilisers

Conveying system Zinc plated steel rollers for longitudinal transfer,

transversal drive units on front platform,

hydraulically adjustable guide rails on front platform

Hydraulic system Central hydraulic valve block, valves fitted with control light

Electric system 24V, relay controlled

Options

Side loading and rotation on rear of main platform (standard at 70W and 70U), electrically powered hydraulic emergency system to lower platforms and lift

stabilisers, dynamic brake system etc.

Please consult the technical specification for further information.



TREPEL Airport Equipment GmbH

Hagenauer Strasse 42 D-65203 Wiesbaden / Germany http://www.trepel.com phone: +49(0)611-880 88-0 fax: +49(0)611-880 88-11 e-mail: airport@trepel.com





