

## Dräger RVP 3900 Visualisation panel

The Dräger RVP 3900 is a high resolution 8,4" Touchpanel for central visualisation and data processing of gas concentration from the central units:  
Dräger REGARD 3900 and Dräger REGARD 3910.



The Dräger RVP 3900 allows the visualisation for up to 128 channels out of maximal 8 Dräger REGARD 3900/3910 gas detection systems. The Dräger RVP 3900 is Plug and Play compatible and no configuration is required. The Dräger RVP 3900 is a very efficient and economic solution for visualisation, analysis and summarisation of gas detection systems.

### PRESENTATION

The gas concentrations can be presented as bar graphs or tables. All relevant data are collected and displayed in detail online:

- name of gas
- type of gas
- measuring range
- gas concentration
- alarms
- faults

### ALARM LOG AND EVENT DISPLAY

Alarms and events can be retrieved easily. Detailed values regarding time, channel and type of alarm or event are provided.

### DATALOGGER (OPTIONAL)

By means of a data logger, measured values and events can be stored up to 31 days for the documentation. There is a userfriendly output of data via CompactFlash® card or USB port. This data can be easily edited for example with Microsoft® Excel.

### WEBINTERFACE (OPTIONAL)

The web interface can be integrated in the local network and allows a comfortable browser access. The web interface provides the possibility of access to all functions of the Dräger RVP 3900 via ethernet or internet.

### NETWORK CONNECTION (OPTIONAL)

Further interfaces can be integrated in superior control systems and company networks which utilise Modbus or Profibus. Communication with more touch panels and connection to external systems is therefore on demand.



Dräger RVP 3900

**TECHNICAL DATA**

Hardware	Touch Panel
Power supply	+ 24 V DC $\pm$ 20 %; 24 watts max.
Display	8,4", 640 x 480 pixels
Interface	RS 485, 2-wire (max. transfer distance 1200 m)
Ethernet	10 Base T/100 Base-TX
Card slot	CompactFlash up to 2 GB Type I and Type II
Protection class	Front side IP66
Ambient temperature (operation / storage)	0 to + 50 °C / - 20 to + 80 °C
Weight	Approx. 1910 g
Housing	Steel with aluminium front plate
Dimensions	262 mm x 208 mm x 56 mm (W x H x D)

**ORDER INFORMATION**

Dräger RVP 3900	SC 00 080
Dräger RVP 3900 Datalogger	SC 00 081
Dräger RVP 3900 WEB (incl. Datalogger)	SC 00 082
Dräger REGARD 3900 Modbus Gateway	SC 00 083
Dräger REGARD 3900 Modbus Gateway Cable	SC 00 084
Dräger REGARD 3910 Modbus Gateway Cable	SC 00 085

**HEADQUARTERS:**

Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Lübeck, Germany

[www.draeger.com](http://www.draeger.com)

**SYSTEM CENTERS:****P. R. CHINA**

Beijing Fortune Draeger  
Safety Equipment Co., Ltd.  
Yu An Lu A 22, B Area  
Beijing Tianzhu Airport  
Industrial Zone  
Houshayu Shunyi District  
Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

**GERMANY**

Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Lübeck  
Tel +49 451 882-2794  
Fax +49 451 882-4991

**FRANCE**

Dräger Safety France SAS  
3c route de la Fédération, BP 80141  
67025 Strasbourg Cedex 1  
Tel +33 3 88 40 59 29  
Fax +33 3 88 40 76 67

**SINGAPORE**

Draeger Safety Asia Pte. Ltd.  
67, Ayer Rajah Crescent # 06 03  
139950 Singapore  
Tel +65 68 72 92 88  
Fax +65 67 73 20 33

**UNITED KINGDOM**

Draeger Safety UK Ltd.  
Blyth Riverside Business Park  
Blyth, Northumberland NE24 4RG  
Tel +44 1670 352 891  
Fax +44 1670 544 475

**USA**

Draeger Safety, Inc.  
505 Julie Rivers, Suite 150  
Sugar Land, TX 77478  
Tel +1 281 498 10 82  
Fax +1 281 498 51 90