

Affinity Folded Respirators

[Gentle as a Summer Breeze]



Affinity FLS

Comfort. Performance. Protection.

Affinity FLS is the new generation of foldable disposable respirators from MSA. Its high-performance thin and light filtering media makes you feel as if you are not wearing a mask, but simply being protected. Affinity FLS feels as gentle as a summer breeze against your face.

Affinity folded respirators offer effective protection against penetrating solid and liquid aerosol particles present in various work environments. Meeting the requirements of EN 149:2001, the different types of mask conform respectively to protection levels FFP1, FFP2 and FFP3. A colour coding system ensures easy identification and helps you select the right kind of mask for any given application.





[Excellent Comfort]

Affinity FLS features extremely light and thin filtering media, providing a comfortable fit even when used for longer periods. The vertical fold ensures an ergonomic face seal. The low-profile design of Affinity FLS makes it ideal for use under welding hoods or in any tight spot where a respirator must be worn. A pre-shaped nose clip allows for easy contour adjustments to achieve a snug fit that prevents exhaled breath from escaping and fogging safety glasses.



[High Performance]

The optional available exhalation valve of Affinity FLS optimises the air flow by removing warm exhaled breath. The reduced temperature and moisture vapour make breathing easier. Affinity is dolomite tested to guarantee better breathing comfort and longer service life, particularly in high dust environments. Due to the exceptional quality of the filtering media, Affinity FLS masks have a storage life of 5 years, from the date of manufacture.



[Optimal Protection]

The smooth inner lining of Affinity FLS provides a secure and comfortable seal. The elastic band ensures easy donning and doffing and a good tight fit for all face and head sizes. Affinity offers "one-size-fits-all" convenience without compromising effectiveness. Due to its individual wrapping, Affinity FLS can be carried on the job, when not in use. Even in dirty environments, it will remain clean and hygienic. With its small size, the respirator fits easily into any pocket, ready for immediate use.

The special Odour Removal version Affinity FR FFP2 offers relief from low-level concentrations of acid gases [including HF], below TLV [nuisance levels].





[Reasons for Choosing Affinity FLS]

	Features	Benefits	
	Thin and light material	Comfortable fit all shift long	
Excellent wearer	Vertical fold	Provides an ergonomic face seal	
comfort	Low profile	Ideal for use in combination with other PPE	
	Pre-formed nose clip	Prevents fogging of safety spectacles	
High performance	Exhalation valve [optional]	Prevents heat build-up and reduces breathing resistance	
	Dolomite tested	Longer service life in high dust environments	
	Smooth inner lining	Provides a tight seal	
Optimal	Elastic head band	Perfectly adapts to different face/head sizes	
protection	Hygienic pocket-size packaging [individually wrapped]	Always ready for use	
	Colour coding according to filter class	Allows quick identification	
Cost effectiveness	Universal size	Reduces inventory and simplifies selection	
cost enectiveness	High filter media quality	Provides 5 years storage life	













[Examples of Applications]

Application	Protection class	Colour code
Grinding, sanding, cutting, sweeping, sawing, bagging	FFP1	Green
Machining, welding, brazing, plastering, insulation installation	FFP2	Yellow
Pharmaceuticals, industrial processes, asbestos environments	FFP3	Red

Service Time

Approvals

Maximum duration of use:

8 hours within one shift [not reusable]

amendment A1:2006 to EN 143:2000]

service life under high dust exposure]









Affinity FLS





Affinity FR [Odour Removal]

[Technical Data]

Materials	
Filter media	Polypropylene
Elastic headband	Natural latex [Affinity FLS] Natural rubber, polyester [Affinity FR]
Valve housing	Polypropylene
Valve membrane	Vulcanized rubber
Nose clip	Steel, polypropylene
Nose foam	Polyurethane
Plastic attachments [Affinity FR]	Polypropylene

5 years, from the date of manufacture [under proper storage conditions]

EN 149:2001
Russia, Kazakhstan: GOST R 12.4.191-99
Belarus: STB GOST R 12.4.191-2006
Ukraine: DSTU EN 149:2004
Tests
120 mg loading test [as required in

Dolomite dust test [resistance to clogging and longer

Affinity FR OR [FFP2]	3 years, from the date of manufacture [under proper storage conditions]

[Ordering Information]

Storage Life Affinity FLS

Affinity FLS	5	Protection class	Units per box	Boxes per carton	Carton size in cm	Carton weight in kg
	Affinity FLS	FFP1 D	15	12	33.5 x 30.5 x 49.0	2.9
10097426	Affinity FLS-V	FFP1 D	15	12	33.5 x 30.5 x 49.0	3.7
10097427	Affinity FLS	FFP2 D	15	12	33.5 x 30.5 x 49.0	3.1
10097428	Affinity FLS-V	FFP2 D	15	12	33.5 x 30.5 x 49.0	3.9
10097429	Affinity FLS-V	FFP3 D	15	12	33.5 x 30.5 x 49.0	4.1

Affinity FR [Odour Removal]	Protection class	Units per box	Boxes per carton	Carton size in cm	Carton weight in kg
10070802 Affinity FR OR	FFP2 D	15	12	33.5 x 30.5 x 49.0	5.3
10070803 Affinity FR-V OR	FFP2 D	15	12	33.5 x 30.5 x 61.0	5.5

V: With exhalation valve

D: Dolomite dust tested

OR: Odour Removal [providing nuisance relief]

For the cup-shaped Affinity Plus line please see leaflet 28-100.2.

Your direct contact

Northern Europe

MSA Nederland B.V., Hoorn Phone +31 [229] 25 03 03 E-Mail info@msaned.nl

Central Europe

MSA AUER GmbH, Berlin Phone +49 [30] 68 86-0 E-Mail info@auer.de

Eastern Europe

MSA Safety Sp. z o.o., Warsaw Phone +48 [22] 711-50 33

E-Mail mee@msa-europe.com ID 28-111.2 GB/00/C/04.09/HA

Southern Europe

MSA EUROPE Regional Head Offices & Great Britain [www.msa-europe.com]

MSA Italiana S.p.A., Rozzano Phone +39 [02] 89 217-1 E-Mail info-italy@msa-europe.com

International Sales

MSA EUROPE, Berlin Phone +49 [30] 68 86-555 E-Mail contact@msa-europe.com

Great Britain

MSA [Britain] Limited, Coatbridge Phone +44 [12 36] 42 49 66 E-Mail info@msabritain.co.uk